

## **U GROUP SRL**

Via Borgomanero n°50 28040 Paruzzaro (NO) LEGAL DATA:

Cap.Soc.:

SR-Slip resistance on ceramic with glycerin (heel back 7°)

C.F e Reg.Imp.Novara: CCIAA Novara REA: P.IVA: Codice Export: 02041920030 211799 IT02041920030 No015724 119.000 lv CONTACTS: WEBSITE: EMAIL: TEL: FAX:

www.u-power.it/it info@u-power.it +39 0322 53 94 01 +39 0322 23 00 01

REV. 01/02/2024

**DATA SHEET** 

PRODUCT PICTURE

**RANGES** 

**TECHNOLOGIES** 

UB20089 GENESIS OB SR Confort 11 SHOE TYPE "A" SIZE RANGE 35-48 Size tested: 42 - WEIGHT 1.038













0.25



D	ES	CRI	PT	ION

The shoe GENESIS is equipped with a soft leather upper with green microfiber inserts, lining and leather tongue that ensures comfort and well-being of the foot.

The perforated toe ensures greater breathability. Comfort is also increased by the leather insole and the polyurethane sole with Infinergy® insert.

Infinergy® insert, the soul of this revolutionary shoe is the technology that stores over 55% of energy and returns it at every step.

Born for the world of running, Infinergy® has transformed the traditional cushioning into dynamic cushioning, which uses the movement of the foot to store energy in the ground grip phase and return it when the foot pushes forward.

The first LIFESTYLE shoe branded U-Power characterized by:

- attractive look
- sporty design
- amazing comfort

	TECHNICAL SPECIFICATIONS		EN ISO STANDARD	VAL	.UE
	SAFETY TOE CAP		20347:2022	RES	ULT
II-	Impact resistance. Free heights after collision mm	≥ 14		N.A.	
	Compressive strength. Free heights after compr. mm INSOLE "N.A."	≥ 14		N.A.	
ed	Puncture resistance N	≥ 1100	)	N.A.	
	ELECTRICAL RESISTANCE CATEGORY	< 10 <sup>9</sup> 0	Ω	N.A.	
	UPPER DYNAMIC WATERPROOFING AFTER 60'				
t	Water absorption after 60'	≤ 30%		N.A.	
	Water transmitted after 60'	≤ 0.2 (	gr	N.A.	
	Permeability to water vapor mg/(cm <sup>2</sup> h)	≥ 0.8		1.0	
t	Permeability coefficient mg/cm <sup>2</sup> VAMP LINING	≥ 15		20.1	
es	Permeability to water vapor mg/(cm <sup>2</sup> h)	≥ 2		16.9	
	Permeability coefficient mg/cm <sup>2</sup>	≥ 20		142.3	
	Resistance to abrasion - DRY cycles	25600	cycles	No hole	
	Resistance to abrasion - WET cycles  INSOLE	12800	cycles	No hole	
	Abrasion resistance SOLE WEAR	≥ 400	cycles	No damage	
	Abrasion resistance (volume loss) mm <sup>3</sup>	≤ 150		28	
	Bending resistance mm	≤ 4		0.8	
	Resistance to sole / midsole detachment N/mm	≥ 3		3.6	
	Heel energy absorption J	≥ 20		N.A.	
	SLIP RESISTANCE Slip registance on coronic with No.L.S. (heal forward 7°)	≥ 0.31		0.45	
	Slip resistance on ceramic with NaLS (heel forward 7°) Slip resistance on ceramic with NaLS (heel back 7°)	≥ 0.31		0.45	
	SR-Slip resistance on ceramic with NaLS (neer back 7 ) SR-Slip resistance on ceramic with glycerin (heel forward 7°)	≥ 0.36 ≥ 0.19		0.42	
	on-only resistance on ceramic with glycerin (neer lorward 1)	≥ 0.19		0.52	

≥ 0.22